Swivel castor:

# G42AZ-RU2K125
# (367a 29K125v ZPF)



## Technical data

| | | |
|---|---|---|
| Diameter | | 125 mm |
| Tread width | | 32 mm |
| Height | | 162,5 mm |
| Offset | | 43,5 mm |
| Top plate dimensions | | 95x70 mm |
| Top plate hole diameter | | 9 mm |
| Dist. between holes | | 75x45/72x52 mm |
| Load capacity | | 100 kg |
| Weight | | 852 g |

## Technical description

- sheet steel metal housing
- zinc passivated
- swivel bearing with double ball race
- protected from dust and water spray with plastic seal
- available with plate PD (77x67 mm) and PF (95x70 mm)
- available with bolt hole LC (10,2 mm) and LD (12,2 mm)
- on inquiry also available with fixing pin Z522 (24x45 mm) and Z622 (28x45 mm)

REACH compliant RoHS compliant

## Wheel

- thermoplastic polyurethane tyre (TPU) iron grey RAL 7011 (Shore A 95)
- plastic wheel centre and thread guard silver grey RAL7001
- free of contact discoloration
- precision ball bearing

A company of Colson Group
Colson Rollen GmbH , Industriestraße 8, D-42499 Hückeswagen,
Tel. +49 2192 9368-0, Fax +49 2192 9368-477, info@colson-rollen.com